


30X IR PTZ HIGH POWER LED DOME

FULL HD IP IR PTZ CAMERA
2MP / WDR / TDN / DNR
DC24V / PoE IEEE




3 Part Insert Bubble

The normal bubble has the light reflection on the lens by being reflected from the inside surface of the bubble. CPRo's 3 part insert bubble has a block part blocking IR light from entering the lens so the light reflection has decreased dramatically.



Vari-IR technology with 30x optical zoom

The angle of the IR is automatically adjusted according to the zoom, and 360° omni-directional monitoring is possible up to 70m at night.



95° tilt supportable at the PTZ

To overcome tilt angle limitation from the normal spherical bubble, the improved bubble provides 95° tilt angle without any image distortions.

More compact than anything else

It is compact and light compared to the same performance PTZ camera in a small simple design that can be installed in/outdoor.

30X IR PTZ HIGH POWER LED DOME

FULL HD IP IR PTZ CAMERA
2MP / WDR / TDN / DNR
DC24V / PoE IEEE




3단 인서트 버블로 IR 난반사 현상 개선

기존 일체형 버블은 IR 빛이 버블 안쪽 표면에서 반사되어 렌즈에 난반사 현상이 일어났습니다. 씨프로의 3단 인서트 버블은 렌즈 및 IR 사이에 가림막을 설치하여 IR 빛이 렌즈로 들어오지 않아 난반사 현상이 없습니다.



PTZ에 최적화된 가변 IR 기술

zoom에 따라 IR의 각도가 자동 조절 되어 야간에 최대 70m 까지 360° 전방위 감시가 가능합니다.



원형돔으로 화각 가림 현상 최소화

개선된 원형돔은 중심축을 위로 올려 5° ~ -90° Tilt를 지원함으로써 반구돔의 화각 가림 문제를 해결했습니다.

동급 PTZ보다 월등히 작고 심플한 디자인

실외 뿐만 아니라 실내에 설치해도 손색 없는 작고 심플한 디자인으로 동급 성능 PTZ 카메라에 비해 월등히 작고 가벼워 설치 및 유지보수가 용이합니다.