

2M IP REPOSITIONING PTZ DOME


NPX3-52

Features

- 2MP PTZ camera
- Maximum resolution 1920 (horizontal) X 1080 (vertical) / 30fps
- Horizontal angle of view 115 degrees (2.8mm) to 59 degrees (8.0mm) / MFZ lens
- Day & Night (ICR)
- Backlight compensation (WDR)
- SD/SDHC/SDXC memory slot
- PoE IEEE 802.3af/Class3
- IP67



Dimension (mm)



Specification

Video

Image Sensor	1/2.8" 2.1M CMOS
Channels	1
Total Pixel	1945(H) X 1109(V)
Max Resolution	1920(H) X 1080(V)
MIN. Illumination	COLOR: 0.03Lux BW: 0.006
Only installer Video Output	1 [CVBS 1.0V p-p (75Ω)]
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens

Focal Length	2.8~8mm
Aperture	F1.6
Lens Type	Motorized_Varifocal
IRIS Type	P-IRIS
Horizontal Angle	D:68.3 ~131.6 , H:59.3 ~114.7 , V:33.2 ~61.2
Pan / Tilt / Zoom	Pan:360 Tilt :90 Zoom :X2.8

Operational

Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	Non-IR
LED Distance	No
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic

AI Intelligent Video Analytic	No
-------------------------------	----

Encoder (video & audio)

Video Compression	H.264 H.265 MJPEG
-------------------	-------------------

Encoder (video & audio)

Support Resolution	H.265 : 1920x1080/1280x720/640x480/352x288/352x240 H.264 : 1920x1080/1280x720/640x480/352x288/352x240 MJPEG : 1920x1080/1280x720/800x600/640x480/768x432/704x576/704x480/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest) Smart LBR

I/O & Event

Audio In / Out	1 Line Input[1.0Vrms, 3K ohm]/1 Line Output
Alarm In / Out	1 Line/1 Line
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3at Class4
Power consumption	DC Max: 11.4W PoE Max: 15.36W

Environmental

Operating Temperature	-20°C ~ 50°C
Cold Start	No

Environmental

Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	No
IP Rating	IP67
Other Certification	FCC CE ROHS KC

Mechanical

Housing Model	PX3
Housing	Outdoor Dome PTZ
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	125mm 116mm
Weight	1kg