

5M IP IR Mini Bullet


NBI2-45-R

Features

- 5MP miniature camera
- Maximum resolution 2592 (horizontal) X 1944 (vertical) / 30fps
- Horizontal angle of view 82 degrees (4.0mm) / Fixed lens options
- Day & Night (ICR) / IR reach distance 31 meters
- Backlight compensation (WDR)
- SD/SDHC/SDXC memory slot
- PoE IEEE 802.3af/Class3
- IP67



Dimension (mm)



Specification

Video

Image Sensor	1/2.8" 5.69M CMOS
Channels	1
Total Pixel	2704(H) X 2104(V)
Max Resolution	2592(H) X 1944(V)
MIN. Illumination	0.16Lux 0Lux with IR (F2.0)
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens

Focal Length	4.0mm
Aperture	F2.0
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	D:106.6 , H:82.3 , V:58.8
Pan / Tilt / Zoom	Zoom :Fixed

Operational

Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	WDR(2x)
Dynamic Range	120dB or above
LEDs	H2IR
LED Distance	100ft(31m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip Auto White Balance

Intelligent Video Analytic

AI Intelligent Video Analytic	No
-------------------------------	----

Encoder (video & audio)

Video Compression	H.264 H.265 MJPEG
-------------------	-------------------

Encoder (video & audio)

Support Resolution	H.265 : 2592x1944/2560x1440/2304x1296/1920x1080/1280x720/704x480/640x480/352x288/352x240 H.264 : 2592x1944/2560x1440/2304x1296/1920x1080/1280x720/704x480/640x480/352x288/352x240 MJPEG : 1920x1080/1280x720/800x600/768x432/704x576/704x480/640x480/352x288/352x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.264,H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	No
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event

Audio In / Out	No
Alarm In / Out	No
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule
Event Notification	FTP E-Mail SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD Micro SDHC Micro SDXC
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 6.5W PoE Max: 8.3W

Environmental

Operating Temperature	-20°C ~ 60°C
Cold Start	No
Operating Humidity	10-90% RH(Non-Condensing)


Environmental

Vandal Proof Casing	No
IP Rating	IP67
Other Certification	FCC CE ROHS

Mechanical

Housing Model	BI2
Housing	Outdoor Bullet
Material	Aluminum-Die Casting
Color	Dark Gray
Dimensions (W x D x H)	160.5mm 67.5mm
Weight	0.5kg

Compatible Accessories



BJC07

Junction Bracket